



Features

- Reactive style silencing design
- Integrated discharge silencer
- Adjustable motor supports for belt tensioning
- Pre-assembled rails to frame
- Easy sheaves accessible belt guard
- Carbon steel with baked enamel finish

Technical Specifications

- Pressure Rating: 1 ATM
- Hardware Kit (USA standard nuts, bolts, washers) included
- Ports for: relief valve, pressure & temperature gauges

Options

- Purpose built belt guard
- Flexible boot kit
- Snubber discharge silencer for vacuum applications
- Contact factory for best Solberg filter for your package

Benefits

- Compact design for small blower package footprint
- Low profile allows for easier maintenance inspections
- Quick installation time
- Cost Savings (Minimal packaging, freight & storage)
- Sound enclosures are more economical due to compact frame footprint



Example of Silencer Base Frame Package

MPT Outlet Connections

Pipe Stub Inlet	MPT Outlet	Assembly m ³ /h Rating	Part Number	Dimensions - mm			Relief Valve Port	Sugg. HP Range	Approx. Wt. kg	Belt Guard for BBF Series	
				A	B	C				Part No.	Weight (kg)
2"	2"	230	BBF-200	597	699	279	2"	3-15+	59	DL-200	9
2 1/2"	2 1/2"	332	BBF-250	597	699	279	2"	3-20+	59	DL-200	9
3"	3"	510	BBF-300	711	889	360	2"	10-30	81	DL-300	10
4"	4"	884	BBF-400	711	889	360	2"	20-50	81	DL-300	10
6"	6" Flg	1870	BBF-600F	883	1003	457	3"	40-60	179	DL-600	13

Note: Model offerings and design parameters may change without notice. See www.solbergmfg.com for most current offering.