Oil Free Compressor

Two-Year Warranty

Features

No pollution, maintenance free

Rocker series pumps are driven by Piston, without the need of lubricant, regular oil changes and maintenance; with no oil pollution.

Quiet and low vibration

Driven direct by motor with no additional belt-driven transmission; the quality vibration-proof assembly makes Rokcer series run at the lowest noise level among all other equivalent pumps.

Thermal protection device

Every motor of Rocker series pumps has a built-in thermal protection device to shut off the pump automatically when overheated and then resume working when the temperature cools down.

Air outlet filter device

Every Rocker series compressor is equipped with filter cartridge in air outlet to filter particle, moisture and supply clean air.

International safety certification
CE certification
CSA certification

Applications

Aeration

Pressure filtration

Ordering Information

167320-11(22) Rocker 320, Compressor AC110V, 60Hz (AC220V, 50Hz)

167420-11(22) Rocker 420, Compressor

AC110V, 60Hz (AC220V, 50Hz)





Specification

Model	Rocker 320		Rocker 420	
Voltage	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Max. power (W)	90	85	147	125
Max. current (A)	0.9	0.4	1.5	0.6
Max. pressure (w/o moisture trap)	100 psi		100 psi	
Max. pressure (w. moisture trap)	80 psi		80 psi	
Max. flow rate	14 l/min	12 l/min	27 l/min	25 l/min
Moisture trap	Yes		Yes	
Motor rotation	1700 RPM	1400 RPM	1700 RPM	1400 RPM
Horse power	1/8 HP		1/6 HP	
Noise level	50 dB		52 dB	
Hose barb	5/16 inch (8 mm)		5/16 inch (8 mm)	
Net weight	4.1 Kg		5.2 Kg	
Dimension (LxWxH)	27.2x 13.6x16.5 cm		29.8x14.3x17.2 cm	

PS: 1 l/min \doteq 0.035 CFM, 1 psi \doteq 0.0698 bar \doteq 0.07 kg/cm²

