

Filtration System for Suspended Solid Test

Two-Year Warranty

Features

- **No air pollution, maintenance free**

Rocker 300 - LF 30 - SS utilizes piston pump requiring no lubricant and regular maintenance.
- **The patented spin-lock design**

The filter holder can be connected with waste bottle by patented spin-lock connection giving a fast and stable installation without clamp.
- **Overflow protection**

The waste bottle has a built-in overflow protection which keeps the filtrate from overflowing into the pump when waste bottle is full.
- **Ideal package**

The complete set of Rocker 300 - LF 30 - SS offers a total solution for suspended solid test.



Rocker 300 - LF 30 - SS

Applications

- Suspended Solid Test

Ordering Information

167307-11(22)

Rocker 300 - LF 30 - SS, Vacuum

Filtration System includes,

* Rocker 300, Vacuum Pump

* LF 30, Filtration Set

* Glass Fiber Filter, 47mm, 1 μm , 100/PK

* Silicone Tube (1m)

Specification

Model	Rocker 300 - LF 30 - SS	
Voltage	110V/60Hz	220V/50Hz
Max. flow rate	22 l/min	20 l/min
Max. vacuum	- 680 mmHg	
Capacity	Funnel : 300 ml, Waste bottle : 1200 ml	
Filter diameter	47 mm / 50 mm	
Effective filtration area	12.5 cm ²	
Hose barb	5/16 inch (8 mm)	
Part	Material	
Filter funnel	PES	
Waste bottle	PC	
Funnel support base	PP	
Funnel lid	PP	
Overflow protection	PP	
Filter	Glass Fiber Discs, 47mm, 1 μm , 100/PK	